

HARDIEPLANK SIDING W/ 4" (100mm)
SMART TRIM AT CORNER

NOTES:
SEE SECTION 6 - ENGINEERING IN THE
LOGIX PRODUCT MANUAL FOR
REINFORCEMENT DETAILS

3/4" (19mm) T&G PLYWOOD SUBFLOOR
1 7/8" ENGINEERED WOOD I-JOIST

2" X 8" PLATE C/W SILL
GASKET AND ANCHOR
BOLT AS PER SPECS

USE 6 1/4" LOGIX TAPER
TOP FOR TOP COURSE OR WHERE
SILL PLATES ARE LOCATED

6 1/4" LOGIX STANDARD FORM

HORIZONTAL REINFORCEMENT
(SEE NOTES)

ACRYLIC PARGING
BELOW SIDING

WATERPROOFING

VERTICAL REINFORCEMENT
(SEE NOTES)

1/2" (13mm) GWB FASTENED
TO WEBS

BACK FILL

FILTER FABRIC

40xREBAR
DIAMETER

4" (100mm) CONCRETE SLAB

4mil VAPOR BARRIER UNDERNEATH

12" (305mm) MIN
3/4" (19mm) DRAINAGE ROCK OVER PIPE

4" (100mm) Ø PERFORATED TILE

6" (152mm) MIN COMPACTED
SAND OR GRAVEL

UNDISTURBED SOIL OR BEDROCK

7'8"
6 ROWS 8'0"



THOMPSON
RIVERS
UNIVERSITY

**Architectural &
Engineering
Technology**

805 TRU Way
KAMLOOPS, BC
V2C 0C8
TEL: 250.828.5000

JOB TITLE

ARET 1200- MATERIALS & APPLICATIONS

DRAWING TITLE

ICF FOUNDATION DETAIL (LOGIX BLOCKS)

SCALE

1"= 1'- 0"

DRAWN BY

TKES

CHECKED

MJM

DATE

18 OCT 19

JOB NO.

1200-10-03

DRAWING NO.

SK3